



TEMPERATURE / HUMIDITY TEST REPORT

Company : Dray Tek Corp.
Address : No. 26, Fu Shing Rd., HuKou County, Hsin-Chu Industrial Park,
Hsin-Chu., Taiwan, R.O.C.
Sample Name : ADSL ROUTER
Model Name : VIGOR2600
Date Received : May. 15, 2002
Date Finished : May. 17, 2002

TESTING LABORATORY ARE ACCREDITED BY :

ISO/IEC/EN17025 General Requirements for the Competence of Calibration and Testing Laboratories.

Approval Certificate No.: LA003/E1

WE HEREBY CERTIFY THAT:

The test shown in the attachment was made in accordance with the procedures indicated. We assume full responsibility for the accuracy and completeness of these tests and vouch for qualifications of all people taking them.

	Name	Signature	Date
Testing Engineer	Yorick Pong		
Approving Manager	I - Chin Chan		

Notes :

1. This report will be invalid if duplicated or photocopied in part.
2. This report refers only to the specimen(s) submitted to test, and is invalid as separately used.
3. This report is invalid without examination stamp and signature of this institute.
4. The tested specimen(s) will be preserved for thirty days from the date issued, if not taken back by the applicant



TABLE OF CONTENT :

1. GENERAL INFORMATION

1.1 DESCRIPTION OF EUT	Page 3
1.2 EUT & PERIPHERALS SETUP DIAGRAM	Page 3
1.3 EUT OPERATING CONDITION.....	Page 3

2. TEMPERATURE / HUMIDITY TEST

2.1 DESCRIPTION OF TEST APPARATUS	Page 4
2.2 LABORATORY AMBIENCE CONDITION.....	Page 4
2.3 REFERENCE DOCUMENT.....	Page 4
2.4 TEST CONDITION	Page 4
2.5 SUMMARY OF TEST	Page 4



1. GENERAL INFORMATION

1.1 DESCRIPTION OF EUT

MANUFACTURER : Dray Tek Corp.

SAMPLE NAME : ADSL ROUTER

MODEL NAME : VIGOR2600

SAMPLE QUANTITY : 2 sets

1.2 EUT & PERIPHERALS SETUP DIAGRAM : None

1.3 EUT OPERATING CONDITION : None



2. TEMPERATURE /HUMIDITY TEST

2.1 DESCRIPTION OF TEST APPARATUS

2.1.1 Temperature and Humidity Chamber PDL-4FP

Description of performance :

Temperature range : -40°C ~ +100°C

Humidity range : 5% ~ 98% (R.H.)

Chamber Capacity : W100 × H100 × D80 (cm)

Date of last calibration : AUG. 08, 2001

Date of calibration due : AUG. 07, 2002

2.2 LABORATORY AMBIENCE CONDITION

Temperature : 24°C ~ 25°C

Relative humidity : 59% ~ 62% (R.H)

2.3 REFERENCE DOCUMENT

The test is following customer specification.

2.4 TEST CONDITION

2.4.1 Low temperature test (Operating)

Temperature : -10°C

Duration time : 24 hours

2.4.2 Temperature/Humidity test (Operating)

Temperature : 50°C

Humidity : 90%(R.H)

Duration time : 24 hours

2.5 SUMMARY OF TEST

The test report is not including product function judgment.