



# FIREBOX M290 & M390

Up to 2.4 Gbps UTM throughput

## ENTERPRISE-GRADE SECURITY FOR SMALL TO MIDSIZE BUSINESSES

Because smaller companies are generally less protected and easier to break into, small business has become the new big target for cyberattacks. The Firebox M290 and M390 firewalls are specifically engineered to defend all types of small businesses against attacks that are no less fierce than those targeting larger organizations. Our unique product architecture enables small and midsize businesses to leverage best-in-class security services – from URL filtering and intrusion prevention to application control and ransomware prevention, minus the cost and complexity of multiple single-point solutions.



"WatchGuard Firebox M series firewalls are well-suited for businesses with rapidly evolving networks who need defense against the latest threats. They offer a remarkable range of security features, intuitive management, and throughput your users need to keep up with the pace of business."

- Hayden Johnston, Operations Director at WYSCOM

#### QUICK AND SIMPLE DEPLOYMENT

With WatchGuard Cloud, IT staff can create and store configuration data in the Cloud (public or private) and have the appliance directly shipped to its destination. Once the device arrives, it can connect to the Cloud for a secure download of its configuration settings, saving your staff travel time and money.

#### AUTOMATION TO THE CORE

WatchGuard Firebox M Series appliances are designed with automation to the core, allowing your IT team to do more with less. The WatchGuard Automation Core makes it possible to deploy from the Cloud, block threats, update signatures, and detect and kill malware, all without lifting a finger.

### UNIFIED SECURITY DEFEATS COMPLEXITY

The WatchGuard Unified Security Platform<sup>™</sup> is a true force multiplier for IT teams. It makes operational ease possible by integrating the WatchGuard Firebox with WatchGuard's authentication, endpoint security, and Wi-Fi solutions to enable comprehensive, multi-layered security. Unifying security into a single platform unlocks efficiencies simply not possible with siloed systems, allowing for automation of frequent manual tasks that take up time.

### A CLOUD'S-EYE VIEW OF YOUR ENTIRE NETWORK

WatchGuard Cloud provides full visibility into your network so that you can make timely, informed, and effective decisions about your network security anywhere, anytime. The platform displays 100+ dashboards and reports that allow you to quickly see high-level trends and anomalies, then drill down into detailed information on each.

### EXPANSION MODULES FOR GREATER PORT DENSITY

The Firebox M Series provides expansion bays that can be used to add network modules to define a configuration that meets the needs of almost any network configuration. Each appliance has an open module bay for expansion modules, with options for 8 x 1 Gb copper, 4 x 1 Gb copper, 4 x SFP, 2 x SFP+, or 4 x 1/2.5/5 Gb multi-speed ports. Network modularity empowers IT pros to customize the port configuration to meet their needs, while ensuring the flexibility to adapt the firewall as their network evolves.

#### **FEATURES & BENEFITS**

- Enterprise-grade prevention, detection, correlation and response from the perimeter to the endpoint with our Total Security Suite.
- Gain critical insights about network security, from anywhere and at any time, with WatchGuard Cloud.
- Built-in compliance reports, including PCI and HIPAA, mean one-click access to the data you need to ensure compliance requirements are met.
- Up to 18 Gbps firewall throughput. Turn on all additional security services and still see up to 2.4 Gbps throughput.

## M290/M390

Firebox	M290	M390	
THROUGHPUT <sup>1</sup>			
UTM (full scan) <sup>2</sup>	1.18 Gbps	2.4 Gbps	
/PN (IMIX)	800 Mbps	1.8 Gbps	
HTTPS Content Inspection (IPS enabled) <sup>3</sup>	696 Mbps	1.32 Gbps	
Antivirus	1.47 Gbps	3.1 Gbps	
PS (full scan)	1.3 Gbps	3.3 Gbps	
Firewall (UDP 1518)	5.8 Gbps	18.0 Gbps	
/PN (UDP 1518)	2.4 Gbps	5.2 Gbps	
CAPACITY			
nterfaces 10/100/1000 4	8x1 Gb	8x1 Gb	
/O interfaces	1 serial/ 2 USB	1 serial/ 2 USB	
Concurrent connections	3,500,000	4,500,000	
New connections per second	34,000	98,000	
/LANs	100	250	
WSM licenses (incl)	4	4	
EDR Core Licenses	75	150	
VPN TUNNELS			
Branch Office VPN	75	250	
Mobile VPN	75	250	
SECURITY FEATURES			
Firewall	Stateful packet inspection, TLS decryption, proxy firewall		
Application proxies	HTTP, HTTPS, FTP, DNS, TCP/UDP, POP3S, SMTPS, IMAPS and Explicit Proxy		
Threat protection	DoS attacks, fragmented & malformed packets, blended threats		
Filtering options	Browser Safe Search, Google for Business		
VPN			
Site to Site VPN	IKEv2, IPSec, Policy and Route Based Tunnels, TLS hub and spoke		
Remote Access VPN	IKEv2, IPSec, L2TP, TLS		
VISIBILITY			
Logging and notifications	WatchGuard Cloud & Dimens	ion, Syslog, SNMP v2/v3	
Reporting	WatchGuard Cloud includes over 100 pre-defined reports, executive summary and visibility tools		
CERTIFICATIONS			
Security	Pending: Common Criteria, F	IPS 140-3	
Safety	NRTL/CB		
Network	IPv6 Ready Gold (routing)		
Hazardous substance control	WEEE, RoHS, REACH		
NETWORKING	,		
SD-WAN	Multi-WAN failover, dynamic path selection, jitter/loss/latency measurement		
Dynamic Routing	RIP, OSPF, BGP	cite	
High Availability			
QoS	Active/passive, active/active		
•	802.1Q, DSCP, IP Precedence By policy or application		
Iramc Management			
Traffic Management	Static DHCP (server client re	av) PPPoE DynDNS	
Traπic Management IP address assignment NAT	Static, DHCP (server, client, re Static, dynamic, 1:1, IPSec tra		

<sup>1</sup> Throughput rates are determined using multiple flows through multiple ports and will vary depending on environment and configuration. Max firewall throughput tested via direct connection using 1518 byte UDP frame based on RFC 2544 methodology. All testing performed on Fireware version 12.6.

<sup>2</sup> UTM throughput is measured using HTTP traffic with AV, IPS, and Application Control enabled, and does not account for all security services available on the appliance.

 $^3$  HTTPS throughput is measured per NetSecOPEN methodology - 256k response with TLS1.2 AES256 + SHA-256.

 $^4$  Firebox M290 and M390 ship with one empty bay that can accommodate one of the following: 8 x 1 Gb copper, 4 x 1 Gb copper, 4 x SFP fiber, 2 x SFP+ fiber, 4 x 1/2.5/5 Gb multi-speed ports. PoE+ not supported on M290 and M390.

Contact your WatchGuard reseller or call WatchGuard directly (1.800.734.9905) for help determining the right model for your network. Visit **www.watchguard.com/sizing** to access the online Product Sizing Tool.

K. WitchGuard			
LEDs		( <b>IVV</b> )	
Power switch	Reset USB Network Interfaces		
. •	CYCYCY I		
	Cooling Fans Power Supp	oly On/ Off Switch	
PHYSICAL AND POWER SPECIFICATIONS	M290	M390	
Product Dimensions (W x D x H)	12.08″ x 17.24″ x 1.73″ (307 mm x 438 mm x 44 mm)	12.08″ x 17.24″ x 1.73″ (307 mm x; 438 mm x 44 mm)	
Product Weight	8.04 lbs (3.65 kg)	8.04 lbs (3.65 kg)	
Shipping Dimensions (W x D x H)	22.71″ x 8.14″ x 17.44″ (588 mm x 648 mm x 200 mm)	22.71" x 8.14" x 17.44" (588 mm x 648 mm x 200 mm)	
Shipping Weight	11.53 lbs (5.23 kg)	11.53 lbs (5.23 kg)	
Power	Single PSU -65W 90-264VAC~, 1.0A/1.5A, 47-63Hz	Single PSU -120W 90-264VAC~, 2.2A/2.4A, 47-63Hz	
Power Consumption	110V AC power: 75W at 45 °C with 57% fan speed	110V AC power: 76W at 45 °C with 64% fan speed	
MTBF	623,087 hours	578,655 hours	
ENVIRONMENT	OPERATING	STORAGE	
Temperature	32 °F to 104 °F (0 °C to 40 °C)	-40 °F to 158 °F (-40 °C to 70 °C)	
Relative Humidity	5% to 90% non-condensing	5% to 90% non-condensing	
Altitude	0 to 9,843 ft at 95 °F (0 to 3,000 m at 35 °C)	0 to 15,000 ft at 95 °F (0 to 4,570 m at 35 °C)	

#### STRONG SECURITY AT EVERY LAYER

Uniquely architected to be the industry's smartest, fastest, and most effective network security products, WatchGuard solutions deliver in-depth defenses against advanced malware, ransomware, botnets, trojans, viruses, drive-by downloads, phishing and much more. Total and Basic Security Suite packages are available on all Firebox solutions.

	SUPPORT	BASIC SECURITY	TOTAL SECURITY
Stateful Firewall	1	1	1
VPN	1	1	1
SD-WAN	$\checkmark$	$\checkmark$	1
Access Portal*	$\checkmark$	$\checkmark$	1
Intrusion Prevention Service (IPS)		$\checkmark$	1
Application Control		$\checkmark$	1
WebBlocker		$\checkmark$	1
spamBlocker		$\checkmark$	1
Gateway AntiVirus		$\checkmark$	1
Reputation Enabled Defense		$\checkmark$	1
Network Discovery		$\checkmark$	1
APT Blocker			1
DNSWatch			1
IntelligentAV**			1
ThreatSync (XDR)			1
EDR Core			1
WatchGuard Cloud Log Data Retention Report Data Retention		90 Days 1 Day	365 Days 30 Days
Support	Standard (24 x 7)	Standard (24 x 7)	Gold (24 x 7)

\*Not available on Firebox T20/T20-W, T25/T25-W, or T35-R. Total Security Suite required for M270, M370, M470, M570, M670, FireboxV and Firebox Cloud.
\*\*Not available on Firebox T20/T20-W, T25/T25-W, or T35-R.

For details, talk to your authorized WatchGuard reseller or visit **www.watchguard.com**.

U.S. SALES +1.800.734.9905 INTERNATIONAL SALES +1.206.613.0895 WEB www.watchguard.com

No express or implied warranties are provided for herein. All specifications are subject to change and expected future products, features or functionality will be provided on an if and when available basis. ©2023 WatchGuard Technologies, Inc. All rights reserved. WatchGuard, the WatchGuard logo, Fireware, and Firebox are registered trademarks of WatchGuard Technologies, Inc. in the United States and/or other countries. All other tradenames are the property of their respective owners. Part No. WGCE67522\_051123